# **OR-T 120**



**Easy** 

**Fast** 

**Ergonomic** 

**Economic** 

**Environmentally-friendly** 

**Patented** 



## **OR-T 120**

# Strapping made easy: Strapping with only one push of a button!

#### Easy

Selectable mode to suit application:

- Fully automatic
- Semi-automatic
- Manual
- Soft tension



#### **Fast**



Regardless of package, size, vertical or horizontal strapping:

• Fully or semi-automatic tensioning, welding, and strap cutting – with only one push of a button

### **Ergonomic**



- Very light weight: 3,4 kg
- Automatic welding function, no keystroke needed
- Consistent strapping
- Automatic strapping reduces operator error

### **Environmentally-friendly**



Latest brushless motor with the latest Li-Ion environmentally friendly battery technology from Bosch:

- · High efficiency motor
- No memory effect
- Recharging at any time
- High number of cycles

Light applications	•
Weight (incl. battery), kg	3,4
Dimensions	
<ul><li>Length, mm</li></ul>	320
<ul><li>Width, mm</li></ul>	138
<ul><li>Height, mm</li></ul>	148
Tensioning force, N	(0) 400-1200
<ul><li>Soft, N</li></ul>	(0) 150–750
Tensioning speed, mm/s	220
Friction-weld seal	•

Battery charger, battery	
Charger supply voltage, V	100, 110, 230
Battery charging time, minutes	20-45*
No of cycles per battery,	
up to	200-300**
Battery: Li-Ion (Bosch)	14,4 V, 1,3Ah

Plastic strap	
Polypropylene (PP)	•
Polyester (PET)	•
Width, mm	9/11–13
Thickness, mm	0,35–0,85

Options		
<ul> <li>Suspension bow</li> </ul>	•	
<ul> <li>Protection plate</li> </ul>	•	

- Protection cover
- \* After 20 minutes, approx 75% charge capacity
- \*\* Depending on strap quality, tension and package

#### Economic

- Energy-efficient strapping system
- More cycles per battery charge
- Cost efficient
- Service-friendly construction
- High quality



Developed and manufactured in Switzerland



www.orgapack.com

ORGAPACK GmbH Packaging Technology Silbernstrasse 14 CH-8953 Dietikon Phone +41 44 745 50 50 +41 44 745 52 16 pt@orgapack.com www.orgapack.com

Certificate ISO 9001 / EN 29001